



BALLSLIDE SERIES

Batten System Selector

6

Hull Make				Model		
Builder				Feature		
Hull LOA	Max. Monohull	12m (40ft)	Sail Area	Max. Monohull	38m ² (409ft ²)	
	Max. Multihull	9m (30ft)		Max. Multihull	30m ² (323ft ²)	

Mast details (if known)

Spar Manufacturer	
Mast Type	
Profile No.	

Mainsail details

Luff Length (P)	
Foot Length (E)	
Qty. Full Length Battens	

NOTE: Check that the hull and spar details are correct for your boat. The mast make may vary depending on the year the boat was built. Ronstan recommends you discuss the batten receptacle and quantity requirements with your sail maker.



Feet required for cars;

RC264xx

For luff groove openings greater than 9mm (3/8").

Feet not supplied with cars.

Feet sold in pairs.

Fasteners included.

See website www.ronstan.com for mast compatibility tables.

RC20111	Qty	Pairs
RC20112	Qty	Pairs
RC20113	Qty	Pairs
RC20114	Qty	Pairs
RC20115	Qty	Pairs
RC20116	Qty	Pairs
RC20117	Qty	Pairs
RC20118	Qty	Pairs



Feet supplied with cars;

RC261xx

RC262xx

RC263xx

For luff groove openings of approximately 4.5mm (3/16").

See website www.ronstan.com for mast compatibility tables.



Feet supplied with cars;

RC265xx

For luff groove openings of approximately 8mm (5/16").

See website www.ronstan.com for mast compatibility tables.

